



- Rear load door detail:
1. Hinge rear door panels constructed of heavy-gauge steel powder coated postal grey.
  2. Latch mechanism secures rear doors- this is the USPS approved standard design.
  3. No USPS arrow lock required for rear doors.

**\* NOTE: Suite F & G versatile 4C mailbox modules require the bottom of the rough opening (R.O.) to be 14 1/8" ± 1/16" from a finished, level floor to achieve the USPS approved installation requirements below.**

- Installation requirements specified in USPS STD-4C include:
1. At least one customer compartment shall be positioned less than 48" above finished floor (AFF).
  2. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
  3. No patron (tenant) lock shall be positioned more than 67" AFF.
  4. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
  5. The USPS Arrow lock shall be positioned 36"- 48" AFF.

PRODUCT SERIES:		VERSATILE™ 4C SUITE G	
		REAR LOAD	
<b>AF FLORENCE</b> manufacturing company	MODEL	4CG2-19R	REV B
	SCALE	1:16	LAST REV DATE 6/24/2009
5935 Corporate Drive • Manhattan, KS 66503 www.florencemailboxes.com • (800) 275-1747	DRAWING NUMBER	DRAWN BY	
A GIBRALTAR INDUSTRIES COMPANY	4CGT219RCS	NBC	