



MAX BUNDLE SIZE		
HEIGHT	WIDTH	LENGTH
4 1/4"	11 3/8"	6 1/4"
3 1/2"	11 3/8"	11 1/2"
3"	11 3/8"	14 3/4"
2 1/2"	11 3/8"	14 3/4"

NOTES:

1. To meet ADA/DOJ, ICC/ANSI, and IBC 2006 compliance for maximum 48" door access, the bottom of the rough opening (R.O.) should be 14 1/8" ± 1/16" above finished floor (AFF).
2. Module may be recessed or surface mounted and coordinates with Florence versatile™ 4C mailbox modules, see installation manual for details.
3. Aluminum construction with durable powder coat finish available in 11 architectural colors.
4. Standard engraving is 1" tall lettering in US Block 1L font.

PRODUCT SERIES: VERSATILE™ COLLECTION BOX
 FRONT LOAD - COORDINATES WITH 4C SUITE I



5935 Corporate Drive • Manhattan, KS 66503
 www.florencemailboxes.com • (800) 275-1747
 A GIBRALTAR INDUSTRIES COMPANY

MODEL	HOPIC	REV	A
SCALE	NONE	LAST REV DATE	7/6/10
DRAWING NUMBER		DRAWN BY	
HOPICS		ADALE	