

Notes:

- 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
- At least one customer compartment shall be positioned less then 48" above finished floor (AFF). No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
- No patron (tenant) lock shall be positioned more than 67" AFF.
- No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
- e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
- ωΝ This 4C mailbox can also be used for private applications.
- The rough opening width for multi-unit 4C installations = (the sum of all actual unit widths) 1%".

PRODUCT SERIES: VERSATILETM 4C FRONT LOAD MAILBOX

17" H x 12" W x 15" D

www.florencemailboxes.com • (800) 275-1747 5935 Corporate Drive • Manhattan, KS 6650 A GIBRALTAR INDUSTRIES COMPANY manutacturing compan

47	ω,	₹ (גע
4C	DRAWING NUMBER	SCALE	MODEL 4
4C13D-07CS	NUMBER	NONE	MODEL 4C13D-07
		LSAT	REV
AFD	DRAWN BY	ST REV DATE 5/15/2014	В