
versatile™ 4C Mailbox, 4C13D-15



COMPARTMENT CHART

	DOOR TYPE	PART NUMBER	Compartment Size	Number	
Ī	MAILBOX	MB1	3" H x 12" W x 15" D	15	
	OUTGOING MAIL	OM2	6-1/2" H x 12" W x 15" D	1	
	PARCEL	PL4	13-1/2" H x 12" W x 15" D	1	
	PARCEL	PL5	17" H x 12" W x 15" D	1	

Notes:

- 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - a. At least one customer compartment shall be positioned less then 48" above finished floor (AFF).
 - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - c. No patron (tenant) lock shall be positioned more than 67" AFF.
 - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
- 2. This 4C mailbox can also be used for private applications.
- 3. The rough opening width for multi-unit 4C installations is provided using the Florence configurator: www.florencemailboxes.com/configurator.

PRODUCT SERIES: VERSATILETM 4C FRONT LOAD MAILBOX



5935 Corporate Drive • Manhattan, KS 66503 800.275.1747 • www.florencemailboxes.com

MODEL 40	^{10DEL} 4C13D-15		В
SCALE NONE		07/09/19	
DRAWING	NUMBER		DRAWN BY
4C	13D-15CS		RAK